

More from the BIOCLAD family



BioClad® antimicrobial hygienic wall cladding



BioDoor®
Severe duty door ranges constructed to client specification or supplied as complete solutions.



BioPod®
Prefabricated wash stations with access panels and basins.

BIO | ARMIS

K13 RICID SHEET BIOCLAD® BIOARMIS® ANTIMICROBIAL WALL AND DOOR PROTECTION SHEETS.

SPECIFICATION

Finish Satin
Thickness 2mm

Max Temperature 60°C

Size 3050mm x 1220mm

Weight 3.5kg per m²

SUITABLE SUBSTRATES

12.5mm plasterboard, mechanically fixed plywood, sand and cement rendering 1:3 with steel trowel finish, dust free good quality fair faced brick or blockwork, ceramic tiles which are securely bonded to substrate and degreased, 9mm (minimum) W.B.P resin bonded to substrate.

METHOD OF FIXING

Sheets are fully bonded to suitable substrate with trowel applied BioClad 2-part polyurethane adhesive or BioClad® 1-part water based acrylic adhesive.

CUTTING

Fine toothed blade jigsaw or circular saw with fine TCT sawblade whilst sheet is supported.

JOINTS

Sheets can be sealed by hot welding providing a seamless finish or joined with matching PVC single-part silicon free trim systems.

BETWEEN SHEET AND FLOOR

Sheets can be overlaid or trim fixed to a vinyl flooring system.

INTERNAL/EXTERNAL CORNERS

BioClad® BioArmis® can be thermoformed on site to provide a seamless uniform corner arrangement or joined with matching BioClad® BioArmis® External corner profiles.

CLEANING

Regular hot soapy water is sufficient for regular cleaning and a mild cleaning product, such as Jif/Cif, is suitable. NOT an abrasive cleaner. Steam cleaning is suitable for stubborn marks. Mild solvents may also be used but under 60°C and power hosed no closer than 600mm.

CHEMICAL RESISTANCE

BioClad® is resistant to a wide range of chemicals found within the medical, healthcare and food production industries – Full chemical resistance data report available upon request.

FIRE RATINGS

UK – BS 476 Part 6 and Part 7 Class 1/0.

BIOCIDAL PRODUCT REGULATION

BioClad® contains silver phosphate glass antimicrobial technology to preserve and prevent degradation caused by microbial growth. Biocide certified by ECHA, FDA, EPA and is BDR compliant. Antimicrobial is an additional line of defence beyond antibacterial with the power to kill fungi, microbes and protozoans as well as bacteria. BioClad's antimicrobial additive is HACCP certified.

WARRANTY/GUARANTEES

Product 20 year warranty. Lifetime warranty on antimicrobial protection.

STORAGE

Sheets to be stored flat and left at ambient room temperature for 24 hours. Minimum temperature 13°C. Maximum Temperature 40°C. Avoid direct sunlight whilst storing.

LIMITATIONS OF USE

Maximum temperature of 60°C. Sheets can NOT be used near naked flame. Full technical information and consultation available from our technical department.

COLOURS

Select as required – Light Grey; Dark Grey; Green; Light Blue; Dark Blue; Cream; White.



Specification downloads at www.ribaproductselector.com

UK & EU
Accreditations



BIO | CLAD

www.bioclad.com

BioClad® UK (Head Office)

Unit 1, Greengate, Cardale Park
Harrogate, HG3 1CY
England, United Kingdom
Telephone: +44 (0) 1423 870 049
Email: sales@bioclad.com

BioClad® Australia

P.O. Box 1337,
Canning Vale, WA 6970
Telephone: +61 (0) 422 819605
Email: sales@bioclad.com.au

BioClad® India

BioClad Chennai
Telephone: +91 44 43162808
Email: muthu@bioclad.com

BioClad® Canada

6600 Coreway Drive
Mississauga, ON L4V 1S6
Telephone: +1-416-966-3332
Email: sales@bioclad.ca