

VIVID COLOUR RANGE WALL CLADDING SPECIFICATION





DETAILED DESCRIPTION

Single skin PVC panel suitable for food manufacturing areas, commercial kitchens, pharmaceutical areas, laboratories etc.

SUITABLE SUBSTRATES:

- · Good quality fair faced brick or blockwork.
- · Sand and cement rendering 1:3 with a steel trowel finish.
- 12.5 mm thick plasterboard.
- · Ceramic tiles which are securely bonded to substrate.
- 9 mm (minimum) W.P.B resin bonded to substrate.
- Pink lightweight plasters are generally not suitable.
- Some surfaces may need PVA sealer subject to site survey.

PRODUCT GUIDANCE

- Fire rating to BS 476-7:1971: Class 1.
- · Fixing: Fixed using PVC Silicone free gasket system and Advanced all over adhesive.
- Components: Site thermoformed angle sections internal/ external corners, UPVC cill details,
 joints and edge trims. As specified BS "food safe" complying with EEC regulations for hygiene
 in for production areas. Directive No 64/483 and the requirement as outlined in statutory
 instruments 454 and 805 (food hygiene).

COLOUR RANGE

Vivid Purple: 065
Vivid Pink: 055
Vivid Red: 056
Vivid Orange: 053
Vivid Olive: 068
Vivid Green: 066
Vivid Blue: 067
Vivid Black: 078
Vivid Steel: 076
Vivid Lime: 059

· Vivid Taxi Cab Yellow: 051

Vivid Aqua: 040Vivid White: 088

Vivid Royal: 015

MANUFACTURER

BioClad | www.bioclad.com | sales@bioclad.com | +44 (0)330 100 0313 Unit A1,Greengate,Cardale Park,Harrogate,North Yorkshire HC3 1CY

Product reference: The Vivid Colour Range Hygienic Wall Cladding

Finish: Gloss

Size (w x h): 1220 x 3050 mm

Thickness: 2.5 mm - Manufacturer's standard.