



BioFloor® 15 YEAR WARRANTY

BioFloor® warrants that its safety floor covering ranges shall perform in accordance with their published specification and shall maintain their features for a period of 15 years.

BioFloor® must be installed using BioFloor® specially formulated adhesives, recommended procedures, maintained in accordance with the BioFloor® cleaning guide, subjected to fair wear and tear and fully inspected before cutting and installation. *For full terms and conditions see the BioFloor® warranty document.

BioFloor® SPECIFICATION

ANTIMICROBIAL	ISO -22196: 2011	Log10 ≥ 4.83 - 99.9%
Flooring type	EN13845 EN13553	Safety Flooring
Roll dimensions	EN426	2.0m x 20m = 40 m2
Overall thickness	EN428	2.0mm
Weight	EN430	2.45kg/m2
Classification	EN649 EN685	Commercial 34 Industrial 43
Sound insulation	ISO140-8	5 dB
Indentation	EN422	≤ 0.10mm
Wear resistance	EN-660-2	GROUP T
SLIP RESISTANCE	Appendix A (Wet Pendulum) Appendix D (Oil-Wet)	P3 R10
Wear layer	EN429	2.0mm
Flexibility	EN435	PASS 20mm mantrel
Dimensional stability	EN434	<0.4%
Chemical resistance	EN 423	Good SRM20 – has good resistance to dilute acids, organic solvents and alkalis
Colour fastness	EN 20105-B02	Method 3 >6
FIRE performance	EN 13501-1 ISO 9239-1 ISO 11925-2 EC95/28 FMVSS302, CMVSS302 BS 6853:1999 BS 476 pt 7 Din 5510-1 CAN/ULC - S102.2 – TESTED	Class Bfl-s1 Critical Radiant Flux ≥8kW/m2 Smoke Obscuration <750% minutes PASS PASS PASS Cat 1b Class1 SF2



BioClad Ltd (UK Head Office) Unit 1, Greengate, Cardale Park, Harrogate, UK, HG3 1GY.
t. + 44 (0)330 100 0313 **e.** sales@bioclad.com **w.** www.bioclad.com

Australia

BioClad Australia
+61 0422 819 605
sales@bioclad.com.au

India

BioClad Chennai
+91 44 43162808
muthu@bioclad.com

Canada

CDS Distribution Inc
+1 416-669-6647
kmotley@rogers.com

UAE

BioClad Dubai
+971 50 4599724
paddy.mcgrath@bioclad.com